

PATENT APPLICATION TRANSMITTAL LETTER

(Large Entity)

Docket No.

INTL-0219-US (P7127)

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Transmitted herewith for filing under 35 U.S.C. 111 and 37 C.F.R. 1.53 is the patent application of:

ROBERT A. ROSENBERG and ANTHONY C. MILLER

For: **LIQUID CRYSTAL OVER SEMICONDUCTOR DISPLAY WITH ON-CHIP STORAGE**

Enclosed are:


- ☒ Certificate of Mailing with Express Mail Mailing Label No. **EL360180325US**
☒ 3 sheets of drawings.
☐ A certified copy of a _____ application.
☒ Declaration ☒ Signed. ☐ Unsigned.
☒ Power of Attorney
☐ Information Disclosure Statement
☐ Preliminary Amendment
☒ Other: **POSTCARD.**

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	25	- 20 =	5	x \$18.00	\$90.00
Indep. Claims	5	- 3 =	2	x \$78.00	\$156.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$760.00
TOTAL FILING FEE					\$1,006.00

- ☒ A check in the amount of **\$1,006.00** to cover the filing fee is enclosed.
☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **20-1504** as described below. A duplicate copy of this sheet is enclosed.
☐ Charge the amount of _____ as filing fee.
☒ Credit any overpayment.
☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: **JULY 30, 1999**


Signature
TIMOTHY N. TROP
REG. NO. 28,994
TROP, PRUNER, HU & MILES, P.C.
8554 KATY FREEWAY, STE. 100
HOUSTON, TX. 77024
713/468-8880
713/468-8883 [FAX]

cc:

APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: LIQUID CRYSTAL OVER SEMICONDUCTOR
DISPLAY WITH ON-CHIP STORAGE

INVENTORS: SCOTT A. ROSENBERG and
ANTHONY C. MILLER

Express Mail No.: EL360180325US

Date: JULY 30, 1999

LIQUID CRYSTAL OVER SEMICONDUCTOR
DISPLAY WITH ON-CHIP STORAGE

Background

This invention relates generally to displays for electronic devices such as computers.

5 Liquid crystal displays (LCD) are used as the displays for a large number of electronic devices including laptop computers, telephones, desktop computers, and televisions. However, the predominant display technology continues to use cathode ray tubes (CRT). Most displays today are designed to interface with the older analog technology
10 standards.

Typical CRTs use a raster update interface. This means that pixels must be repeatedly traced in a linear fashion from left to right across the display and from top to bottom. This scanning occurs at a relatively high rate
15 because the image elements of the CRT glow for only a short period of time. Thus, these image elements or phosphors must be frequently refreshed in order to give the appearance of constant light.

Because of the prevalence and widespread acceptance of
20 CRTs as displays for electronic devices, most displays, including liquid crystal displays, tend to match the CRT interface paradigm. Thus, most displays are not designed to have their images persist for a relatively longer time

because the raster interface paradigm guarantees that the image is quickly refreshed.

5 The display refresh controller which provides the refresh signals for the display may use an interface bus that is also used by a graphics processor and general purpose microprocessor in the host system. In addition, the controller may make use of the system memory that other system level devices utilize. Thus, the continuing demands for display refresh tend to tax the available system
10 resources. This means that some portion of the available system bandwidth must be dedicated to supporting the display refresh operation. This may adversely affect bandwidth and potentially decrease system performance.

15 The need to periodically refresh the information in the display takes up some of the bandwidth that could be used to increase the resolution of the display. In addition, some of the available bandwidth could be used to provide higher rate images if that bandwidth were not consumed in supplying redundant information to the display.

20

Summary

A display includes a semiconductor substrate. A liquid crystal over semiconductor pixel array is formed in the substrate. A memory coupled to the array is also formed in the substrate.

Brief Description of the Drawings

Fig. 1 is a schematic cross-sectional view of one embodiment of the display in accordance with the present invention;

5 Fig. 2 is a more detailed enlarged, cross-sectional view of a display of the type shown in Fig. 1;

Fig. 3 is a block diagram of a display in accordance with one embodiment of the present invention;

10 Fig. 4 is a system level block diagram of another embodiment of the present invention;

Fig. 5 is a schematic diagram of one cell of the display in accordance with another embodiment of the present invention; and

15 Fig. 6 is a schematic diagram of a display implementing one embodiment of the present invention.

Detailed Description

Referring to Fig. 1, an electro-optical device 10, such as a spatial light modulator (SLM), may include a plurality of reflective mirrors 12 defined on a semiconductor substrate 14 in accordance with one embodiment of the present invention. Advantageously, the device 10 is implemented using liquid crystal over semiconductor (LCOS) technology. LCOS technology may form large screen projection displays or smaller displays (using direct view rather than projection technology). With LCOS technology, the liquid crystal display is formed in

20

25

association with the same substrate that forms complementary metal oxide semiconductor (CMOS) circuit elements. The display may be a reflective liquid crystal display.

5 The device 10 may include a silicon substrate 14 with a metal layer defining the mirrors 12. The mirrors 12 may be the mirrors of an electro-optic display such as a liquid crystal display. For example, the mirrors 12 may be part of spatial light modulator (SLM) for one of the color
10 planes of a tricolor display. Potentials applied to the mirrors 12 alter the liquid crystal to modulate the incoming light to create images which then can be directly viewed or projected onto a projection screen.

Referring to Fig. 2, each cell or pixel of the display
15 may include a reflective mirror 24 forming one of the mirrors of one of the pixels 12 shown in Fig. 1. In one embodiment of the invention, each cell may be rectangular or square and a slight spacing may occur between each adjacent mirror 24. Thus, a rectangular array of mirrors
20 24 may form an array of pixel elements in conjunction with liquid crystal material 20 positioned over the mirrors 24.

The LCOS structure includes a silicon substrate 14 having doped regions 32 formed therein. The doped regions 32 may define transistors for logic elements and/or memory
25 cells which operate in conjunction with the display pixels as will be described hereinafter. Four or more metal

layers may be provided, including a metal one layer 30 which is spaced by an inter-layer dielectric (ILD) 31 from a metal two layer 28 and a metal three layer 26. A metal four layer may form the pixel mirrors 24. Thus, for
5 example, the metal two layer 28 may provide light blocking and the metal one layer may provide the desired interconnections for forming the semiconductor logic and memory devices. The pixel mirrors 24 may be coupled, by way of vias 32, with the other metal layers.

10 A dielectric layer 22 may be formed over the mirror 24. A liquid crystal or electro-optic material 20 is sandwiched between a pair of buffered polyimide layers 19a and 19b. One electrode of the liquid crystal device is formed by the metal layer 24. The other electrode is
15 formed by an indium tin oxide (ITO) layer 18.

A top plate 16 may be formed of transparent material. The ITO layer 18 may be coated on the top plate 26. The polyimide layers 19a and 19b provide electrical isolation between the capacitor plates which sandwich the electro-
20 optic material 20. However, other insulating materials may be coated on the ITO layer 18 in place of or in addition to the polyimide layers.

Using the LCOS structure, for example as depicted in Fig. 2, a memory element or array may be incorporated into
25 the same silicon substrate which includes the pixel array. In one embodiment of the present invention, a separate

memory array 36 may be included on the same substrate 14 that includes the pixel array 42, as shown in Fig. 3. The memory array may be, for example, dynamic random access memory (DRAM).

5 The memory array 36 receives and transmits data, as indicated by the arrows on the left side of the array 36 from a display controller in a host processor-based system (not shown in Fig. 3). The array 36 also communicates with the pixel array 42 via a refresh circuit 38 utilized for
10 both DRAM memory refresh and pixel array refresh. A digital to analog converter 40 converts the data from the memory 36 to an analog format for addressing particular pixels in the pixel array 42. Moreover, the refresh circuit 38 may feed back to the memory array 36 so that the
15 refresh circuit 38 not only refreshes the pixels in the pixel array 42 but also refreshes the memory array 36.

 Thus, in the process of rewriting the DRAM cells for their own refresh, the same refresh circuitry also updates the pixel cells. Since DRAM and pixel refresh cycles are
20 combined into one cycle, the overall read bandwidth, sourced from the DRAM array, may be reduced. Compared to systems where two separate streams of data are simultaneously read out of the DRAM array, less bandwidth may be used. By using only one stream for both refresh
25 operations, combining the memory and refresh cycles into

one cycle, the overall bandwidth required from the DRAM memory is reduced.

In refresh embodiments, flexibility may be achieved in the number of DRAM bits allocated per pixel cell. In some applications, for instance, the creation of multiple low accuracy buffers may be more advantageous than the creation of a single high accuracy buffer. Because the internal scan process produces additional margin, memory bits may be transferred to the pixel array in many ways using embodiments of the present invention.

Referring next of Fig. 4, a processor-based host system 51 for the electro-optical device 10 includes a system memory 43 which is coupled through an interface bus 44 with a general purpose microprocessor 46 in accordance with one embodiment of the invention. The interface bus 44 also may provide processor and memory access to a media or graphics processor 48 and a display refresh controller 50. The display refresh controller is coupled by a bus 49 to the electro-optic device 10 which may be an LCOS display with integrated storage.

In systems that do not modulate the liquid crystal display in an analog fashion, no digital to analog conversion may be used. Values may be read directly from the storage array and used to modulate the pixel elements in the time domain. Such systems are often called pulse-width-modulation (PWM) systems. For example, a 50%

brightness value stored in a storage array may entail turning the pixel cell on for half of a frame time and then off for the second half of the frame time.

In other cases, a digital to analog converter may
5 convert data from the memory to an analog gray scale format for use by a pixel array. For example, an entire column or more of pixel values may be read from the storage array into an on-chip register. These values may be converted to analog values in parallel and driven into the pixel array.

10 One electro-optical device 10 which may not need a periodic display refresh in some embodiments, is illustrated in Fig. 5. If the periodic display refresh is eliminated, this may also increase the available system wide bandwidth. The illustrated embodiment uses integrated
15 memory 60 for each pixel cell 12. In some embodiments, pixel information may be passed through a digital to analog converter (DAC) 62 to produce gray scale information. The particular manner in which pixels are arranged in the storage array and converted to analog signals may vary by
20 implementation.

Each pixel metal electrode or top metal 12 may be coupled to a separate DAC 62. In one embodiment of the present invention, the DAC may be an eight bit DAC coupled to eight one bit storage elements 60. Each storage element
25 60 may, for example, be a static random access memory (SRAM) cell. Each one bit storage element 60 may be

coupled by a transfer transistor 58 to a different row 56
and a column 54. Thus, the information which is used to
refresh the metal mirror 12 may be stored in the memory 60.
When it is desired to change the pixel information to
5 change the displayed image, then the information in the
memory 60 is refreshed.

Since the display refresh controller only needs to
refresh new information to the display, the overall drain
on the computer system including the buses and memory may
10 be reduced, potentially yielding better performance out of
the other components in the computer system which rely on
these limited resources. In addition, the amount of
redundant information flowing to the display may be
reduced, allowing more new information to be sent to the
15 display. This potentially enables the display of higher
resolution or higher rate images.

In one embodiment of the present invention, a
projection display 64 includes the spatial light modulators
66, 74 and 76, using liquid crystal over silicon technology
20 with integrated memory. The reflective liquid crystal
display projection system 64 typically includes a modulator
or display panel (LCD display panels 74, 66 and 76) for
each primary color that is projected onto a screen 92. In
this manner, for a red-green-blue (RGB) color space, the
25 projection system 64 may include an LCD display panel 74
that is associated with a red color band, an LCD display

panel 66 that is associated with the green color band and LCD display panel 76 that is associated with the blue color band. Each of the LCD display panels 66, 74 and 76 modulates light from the light source 94 and the optics 96 that form red, green and blue images, respectively, and add together to form a composite color image on the screen 92. To accomplish this, each LCD display panel receives electrical signals indicating the corresponding modulated beam image to be formed.

More particularly, the projection display 64 may include a beam splitter 86 that directs a substantially collimated white beam 98 of light, provided by the light source 94, to optics that separate the white beam 98 into red 82, blue 78 and green 102 beams. In this manner, the white light beam 98 may be directed to a red dichroic mirror 72 that reflects the red beam towards the LCD display panel 74 that, in turn, modulates the red beam 82. The blue beam passes through the red dichroic mirror to a blue dichroic mirror 70 that reflects the blue beam towards the LCD panel 76 for modulation. The green beam 102 passes through the red and blue dichroic mirrors for modulation by the LCD display panel 66.

For reflective LCD display panels, each LCD display panel 66, 74 and 76 modulates the incident beam and reflects the modulated beams 90, 100 and 68 respectively, so that the modulated beams return on the paths described

above to the beam splitter 86. The beam splitter 86, in turn, directs the modulated beams through projection optics such as a lens 88, to form modulated beam images that ideally overlap and combine to form the composite image on the screen 92. Each of the panels 66, 74, and 76 may be implemented using liquid crystal over semiconductor technology as illustrated for example in Fig. 2.

While the present invention has been described with respect to a limited number of embodiments, those skilled in the art will appreciate numerous modifications and variations therefrom. For example, while a projection display is described, the present invention may be used in direct view displays as well. It is intended that the appended claims cover all such modifications and variations as fall within the true spirit and scope of this present invention.

What is claimed is:

1 1. A display comprising:
2 a semiconductor substrate;
3 a liquid crystal over semiconductor pixel array
4 formed in said substrate; and
5 a memory coupled to said array, said memory also
6 formed in said substrate.

1 2. The display of claim 1 wherein said pixel array
2 includes a plurality of pixels each including a memory
3 cell.

1 3. The display of claim 2 wherein said memory cells
2 are static random access memory cells.

1 4. The display of claim 1 wherein said pixel array
2 is coupled to said memory by a digital to analog converter.

1 5. The display of claim 1 wherein said memory
2 includes a cell associated with each of a plurality of
3 pixels of the pixel array.

1 6. The display of claim 1 wherein said pixel array
2 forms a reflective liquid crystal spatial light modulator.

1 7. The display of claim 1 wherein said memory a
2 dynamic random access memory, and said display includes a

3 refresh circuit, said refresh circuit adapted to refresh
4 both said dynamic random access memory and said pixel
5 array.

1 8. The display of claim 1 wherein said pixel array
2 is adapted to eliminate the need for a periodic pixel
3 refresh cycle.

1 9. A method for displaying information comprising:
2 forming a pixel array in a liquid crystal over
3 semiconductor substrate; and
4 forming a memory in said liquid crystal over
5 semiconductor substrate, with said memory coupled to said
6 pixel array.

1 10. The method of claim 9 wherein forming a memory
2 includes forming a memory associated with each pixel of
3 said pixel array.

1 11. The method of claim 9 wherein forming a memory
2 includes forming a volatile memory and refreshing said
3 volatile memory and said pixel array in the same refresh
4 cycle.

1 12. The method of claim 9 including displaying
2 information without using a periodic refresh cycle.

1 13. A display comprising:
2 a memory array;
3 a pixel array; and
4 a refresh circuit coupled to said memory array
5 and said pixel array, said refresh circuit adapted to
6 refresh said memory array and said pixel array.

1 14. The display of claim 13 wherein said memory array
2 and said pixel array are formed in the same semiconductor
3 substrate with said refresh circuit.

1 15. The display of claim 14 wherein said substrate is
2 a liquid crystal over semiconductor substrate, said pixel
3 array including a plurality of electrodes adapted to
4 interact with a liquid crystal material over said pixel
5 array.

1 16. The display of claim 13 wherein said memory array
2 is formed of dynamic random access memory.

1 17. A method for displaying information comprising:
2 providing a pixel array in a semiconductor
3 substrate;
4 providing a memory array in said substrate; and
5 refreshing said memory array and said pixel array
6 in the same refresh cycle.

1 18. The method of claim 17 including forming said
2 memory and pixel arrays in a liquid crystal over
3 semiconductor substrate.

1 19. The method of claim 17 including storing pixel
2 data in said memory array.

1 20. The method of claim 17 including providing a
2 liquid crystal material over said pixel array.

1 21. A processor-based system comprising:
2 a processor;
3 an interface bus coupled to said processor; and
4 a display coupled to said processor, said display
5 including a liquid crystal over semiconductor substrate,
6 said substrate including a memory array and a pixel array
7 coupled to said memory array.

1 22. The system of claim 21 wherein said memory array
2 includes a plurality of cells, each cell coupled to a pixel
3 of said pixel array.

1 23. The system of claim 22 wherein said memory cells
2 are static random access memory cells.

1 24. The system of claim 23 wherein said pixel array
2 is a reflective liquid crystal array.

1 25. The system of claim 24, said memory including a
2 plurality of storage locations at each pixel and a digital
3 to analog converter coupling each of said storage locations
4 to a different pixel cell.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220

LIQUID CRYSTAL OVER SEMICONDUCTOR
DISPLAY WITH ON-CHIP STORAGE

Abstract of the Disclosure

5 A display device, such as a projector system, may include a plurality of display panels formed from liquid crystal over semiconductor substrates which incorporate not only the pixel elements but memory as well. The presence of memory in the display allows a host system, such as a computer, to send only new picture information to the display and avoid the transmission of information that does not change. Thus, the display update bandwidth required of the host system may be reduced, allowing the host system to use resources typically required by the display update process for improved performance of other operations. In addition, the elimination of redundant information being transmitted to the display may allow more new information to be transmitted, enabling, for example, a higher resolution display.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

LIQUID CRYSTAL OVER SEMICONDUCTOR DISPLAY WITH ON-CHIP STORAGE

the specification of which

X	is attached hereto.
	was filed on _____ as
	United States Application Number _____
	or PCT International Application Number _____
	and was amended on _____
	(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):			Priority Claimed	
Number	(Country)	(Day/Month/Year Filed)	Yes	No
Number	(Country)	(Day/Month/Year Filed)	Yes	No
Number	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under title 35, United States Code, Section 119(e) of the United States provisional application(s) listed below:

_____	_____
(Application Number)	(Filing Date)
_____	_____
(Application Number)	(Filing Date)



I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

_____	_____	_____
(Application Number)	Filing Date	(Status-patented, pending, abandoned)
_____	_____	_____
(Application Number)	Filing Date	(Status-patented, pending, abandoned)

I hereby appoint Timothy N. Trop, Reg. No. 28,994; Fred G. Pruner, Jr., Reg. No. 40,779, Dan C. Hu, Reg. No. 40,025; Coe F. Miles, Reg. No. 38,559, and John R. Merkling, Reg. No. 31,716 my patent attorneys, of TROP, PRUNER, HU & MILES, P.C., with offices located at 8554 Katy Freeway, Ste. 100, Houston, TX 77024, telephone (713) 468-8880, and Joseph R. Bond, Reg. No. 36,458; Richard C. Calderwood, Reg. No. 35,468; Sean Fitzgerald, Reg. No. 32,027; David J. Kaplan, Reg. No. 41,105; Leo V. Novakoski, Reg. No. 37,198; Naomi Obinata, Reg. No. 39,320; Thomas C. Reynolds, Reg. No. 32,488; Steven P. Skabrat, Reg. No. 36,279; Howard A. Skaist, Reg. No. 36,008; Steven C. Stewart, Reg. No. 33,555; Raymond J. Werner, Reg. No. 34,752; and Charles K. Young, Reg. No. 39,425; my patent attorneys, of INTEL CORPORATION; with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to Timothy N. Trop, TROP, PRUNER, HU & MILES, P.C., 8554 Katy Freeway, Ste. 100, Houston, TX 77024 and direct telephone calls to Timothy N. Trop, (713) 468-8880.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor: SCOTT A. ROSENBERG	
Inventor's Signature: 	Date: 6/28/99
Residence: PALO ALTO, CALIFORNIA	Citizenship: U.S.A.
Post Office Address: 875 UNIVERSITY AVENUE, APARTMENT 9, PALO ALTO, CALIFORNIA 94301	
Full Name of Second/Joint Inventor: ANTHONY C. MILLER	
Inventor's Signature: 	Date: 7/1/99
Residence: GILBERT, ARIZONA	Citizenship: U.S.A.
Post Office Address: 1811 E. LEXINGTON AVENUE, GILBERT, ARIZONA 85234	

INTL-0219 -US (P7127)